



135SL

60020-0000 & 60020-0024

135SL Remote Control Searchlight

Features:

- Constructed of noncorrosive materials
- Sealed beam halogen lamp
- Remote control and 15' cable included
- Long life gear drive.
- Low amp draw
- Patented clutch mechanism prevents motor damage when running against limit stops

Specifications:

Body: White thermoplastic,
 Voltage: 12 or 24 Vdc, Power: 50 Watts
 Horizontal Movement: 320, Vertical Movement: 75
 CandlePower: 100,000, Range @ 1 Lux: 665 ft 202m
60020-0000: 12V
60020-0024: 24V
60030-0000: Control Unit (Switch for the above)

146SL Remote Control Searchlight

60080-0012: 146SL-12VDC, Fuse 10 Amp.
 60080-0024: 146SL-24VDC, Fuse 5 Amp.

Features:

- High Output Halogen Sealed Beam Lamp.
- Weather Resistant Remote control and 15' cable included.
- Sleek Design.
- Rugged Construction.
- Corrosion Resistant Housing

Specifications:

Body: White thermoplastic
 Voltage: 12 or 24 Vdc, Power: 50 Watts
 Horizontal Movement: 360, Vertical Movement: 30 Up, 30 Down
 CandlePower: 175,000, Range @ 1 Lux: 1275 ft 386 m



146SL

60080-0012 & 60000-0024



255SL

60010-2012 & 60010-2024

255SL Remote Control Searchlight

60010-2012: 255SL-12VDC, Fuse 10 Amp.
 60010-2024: 255SL-24VDC, Fuse 5 Amp.

Features:

- Twin High Output Sealed Beam Lamps.
- Remote control and 25' cable included.
- Sleek Design.
- Rugged Construction.
- Tough Polyurethane Finish

Specifications:

Body: White thermoplastic
 Voltage: 12 or 24 Vdc
 Horizontal Movement: 360
 Vertical Movement: 30 Up, 30 Down
 CandlePower: 200,000
 Range @ 1 Lux: 1040 ft 315 m