



## FULLY AUTOMATIC BILGE PUMPS - AUTO-EYE SERIES



	TMC-30605		TMC-30610		TMC-30615	
<b>CAPACITY:</b>	<b>500GPH (1890LPH)</b>		<b>1000GPH (3786LPH)</b>		<b>1500GPH (5676LPH)</b>	
<b>MOTOR:</b>	<b>12V</b>	<b>24V</b>	<b>12V</b>	<b>24V</b>	<b>12V</b>	<b>24V</b>
<b>AMP DRAW:</b>	<b>1.6A</b>	<b>0.8A</b>	<b>4.5A</b>	<b>2.5A</b>	<b>9A</b>	<b>4.5A</b>
<b>FUSE SIZE:</b>	<b>2.5A</b>	<b>1.5A</b>	<b>6A</b>	<b>4A</b>	<b>12A</b>	<b>6A</b>
<b>HOSE DIA.:</b>	<b>3/4" (19mm)</b>		<b>1" (25mm)</b>		<b>1" (25mm)</b>	

- TMC AUTO-EYE SERIES OF SUBMERSIBLE BILGE PUMPS ARE EQUIPPED WITH BUILT-IN ELECTRONIC CONTROLLED REED SENSOR SYSTEM TO MAKE FULLY AUTOMATIC OPERATION EASY.
- NO SEPARATE FLOAT SWITCH IS NEEDED AND RELAY LOOP DESIGN PROTECTS THE PUMP AGAINST INSTANT HIGH CURRENT.
- NO POWER USE UNTIL PUMP TURNS ON WHEN WATER RISES.
- AUTO-EYE PUMPS ARE BUILT WITH COMPACT, EFFICIENT, LONG LIFE MOTOR, RUST AND CORROSION PROTECTED S.S. SHAFT, AND HIGH-IMPACT DURABLE PLASTIC HOUSING.
- QUICK RELEASE STRAINER FOR EASY CLEANING.