



401STC & 403STC

401STC & 403STC :Tournament Series livewell Pumps

401STC : For Thru-Hull Applications Straight 4-3/4" (121mm) Pickup Tube.

Specifications:

Flow Rate: 500 gph /1893 lph, Discharge : 3/4 inch: 19 mm

Voltage : 12 Vdc, Amp Draw : 2.1 amp, Fuse Size : 2.5 amp

403STC : For Thru-Hull Applications Straight 4-3/4" (121mm) Pickup Tube.

Specifications:

Flow Rate: 800 gph /3028 lph, Discharge : 3/4 inch: 19 mm

Voltage : 12 Vdc, Amp Draw : 2.8 amp, Fuse Size : 5.0 amp

209FDP : Tournament Series, Dual Port 1600 Livewell Pump

Engineered to withstand the rigors of tournament fishing, the Tournament Series pump is the highest capacity Livewell pump in today's market. This model features a glass filled nylon dual port base for optional washdown pump connection, Anti-Airlock feature, and a heavy duty long life motor.

Specifications:

Flow Rate: 1600 gph/6056 lph, Voltage : 12 Vdc, Inlet Ports : 1 inches:25 mm

Discharge : 1 1/8 inch:28.6 mm



209FDP



98A-12 & 98A-24

Shower Drain Systems, Multi-Port Inlet 12V & 24V

Specifications: Flow Rate: 800 gph /3028 lph,

Inlet Ports : 3/4, 3/4, 1, 1 1/8, 1 1/2 inches: 19, 19, 25, 28.6, 38 mm

Discharge : 3/4 inch: 19 mm, Size(L x W x H) : 8 1/4 x 11 1/4 x 5 1/2 inches

Size (Length x Width x Height) : 209.5 x 286 x 140 mm

98A-12 : Voltage : 12 Vdc , Amp Draw : 2.8 amp, Fuse Size : 5 amp

98A-24 : Voltage : 24 Vdc , Amp Draw : 1.3 amp, Fuse Size : 2.5 amp

50070-0040 : Impeller removal tool Impeller diameters 40 - 65mm (1 9/16" - 2 9/16")

50070-0080 : Marine Impeller Puller 40 - 57mm (1 9/16" - 2 1/4")(compact version)

50070-0200 : Impeller removal tool: impeller diameters up to 118mm (4 5/8") 65 - 118mm (2 9/16" - 4 5/8")



50070-0040, 50070-0080 & 50070-0200